

MULTIDRAIN UV 600

SUBMERSIBLE DRAINAGE PUMPS



- 10 mm free passage
- Discharge 2" (horizontal and vertical)
- Automatic self-ventilation
- Emerged operation due to motor jacket cooling (S1)
- Thermal motor protection
- Duplex mechanical seal
- Replaceable moisture sealed cable inlet
- Easy to maintain due to guide rail system

DESCRIPTION

The submersible drainage pumps Multidrain UV 600 have been developed for drainage applications where high delivery heads are required.


All kind of drainage / greywater with solids up to 10 mm can be disposed from large depths. Shopping centers, high-rise buildings, undergrounds stations and other buildings with deep basements are the right environment for the UV 600 pumps.

In addition to a fix sump installation these pumps can also be used for mobile applications.

The pressure pipe can be connected either to the vertical or the horizontal discharge.

The horizontal one is suitable for sump installations with a guide rail system (GR 50). For mobile applications or in narrow sumps the connection to the vertical discharge port is recommended.

PERFORMANCE



Type	Delivery head H [m]	6	8	10	12	14	16	18	20	22	24
UV 620-1	Flow rate Q [m³/h]	36	33	30	27	22	16				
UV 620-3		37	34	32	28	24	18	5			
UV 625-3		38	36	33	31	27	23	18	5		
UV 635-3				39	37	34	32	28	25	20	14

We reserve the right to change specifications without notice. Pump performance is subject to ISO 9906 tolerances

The minimum flow velocity in the pressure piping must be 0.7 m/s according to EN 12056. This data is represented in the performance curve as a limit of application.

MULTIDRAIN UV 600

SUBMERSIBLE DRAINAGE PUMPS

SCOPE OF SUPPLY

Pump with 10 m cable, automatic version with integrated ball-float switch, plug 2" with automatic ventilation for the outlet not in use.

Special technical note for UV 620-1 / UV 620-1 S:

Due to the high starting current, the approval of the responsible power supplier should be obtained before commissioning these two pump types.

MECHANICAL DATA

Pump	Vertical single-stage	Oil chamber	Yes
Free passage	10 mm	Seal on medium side	SiC mechanical seal
Bearing	Ball bearings, grease-lubricated	Run dry protection	Yes
Seal on motor side	Mechanical seal	Submersible	Yes
		Pressure outlet	IG 2"

ELECTRICAL DATA

Power line	10m H07RN8-F	Insulation class	F
Type of enclosure	IP 68	Winding thermostat	Yes

MULTIDRAIN UV 600


Type	Code No.	Voltage	Motor rating		Current	Wires	Motor protection	Plug	Weight
			P1	P2					
Without level control									
UV 620-1	JP47337	1/N/PE~230 V	2.40 kW	1.65 kW	10.4 A	3G1,5	Integrated	Without	23.0 kg
UV 620-3	JP47339	3/PE~400 V	2.38 kW	1.95 kW	4.6 A	4G1,0	on request ¹	Without	23.0 kg
UV 625-3	JP47341	3/PE~400 V	2.80 kW	2.28 kW	5.2 A	4G1,0	on request ¹	Without	23.0 kg
UV 635-3	JP47343	3/PE~400 V	3.70 kW	3.05 kW	6.2 A	4G1,0	on request ¹	Without	25.5 kg
With built-in level control									
UV 620-1 S	JP47338	1/N/PE~230 V	2.40 kW	1.65 kW	10.4 A	3G1,5	Integrated	Safety	23.5 kg
UV 620-3 S	JP47340	3/PE~400 V	2.38 kW	1.95 kW	4.6 A	4G1,0	on request ¹	Without	23.5 kg
UV 625-3 S	JP47342	3/PE~400 V	2.80 kW	2.28 kW	5.2 A	4G1,0	on request ¹	Without	23.5 kg
UV 635-3 S	JP47344	3/PE~400 V	3.70 kW	3.05 kW	6.2 A	4G1,0	on request ¹	Without	26.0 kg

¹Protective motor plug necessary see accessory


MULTIDRAIN UV 600

SUBMERSIBLE DRAINAGE PUMPS

Dimensions UV 600 (mm)



Example of single unit installation with GR




48570-00

Single unit 2" with GR 50: sump area min. 40x70 cm
 Single unit 2" without GR: sump area min. 40x50 cm

Duplex unit 2" with GR 50: sump area min. 70x70 cm
 Duplex unit 2" without GR: sump area min. 50x70 cm

In case of installation beneath the backpressure level the pressure tube must be taken in a

Example of duplex unit installation



3 48571-00

loop over the local backup level acc. to EN 12056. Besides, it must be secured with an EN 12050-4-proofed swing-type check valve. Additionally we recommend an alarm system.










In accordance with EN 12056-4 section 5.1, it has a built-in automatic spare pump or a double attachment included, which ensures that sewage drainage is not interrupted.

Suspend control unit in a dry room




MULTIDRAIN UV 600

SUBMERSIBLE DRAINAGE PUMPS

MECHANICAL ACCESSORY

				Code No.	
	① Swing-type check valve	R50 EN 12050-4	2" (DN 50), PN 4	150x120 (HxB)	JP00326
	Ball-type check valve	K50 EN 12050-4	2" (DN 50), PN 6	185x155 (HxB)	JP44782
	② Stop valve		brass, 2" (DN 50), PN 16	140x70 (HxB)	JP44787
	③ Elastic connection		2" (DN 50), PN 4	150x63 (HxD)	JP44775
	④ Hose band clamp		2"		JP44764
	⑤ Hose coupling	Coupling Storz C	2" male thread		JP50217
		Coupling wrench			JP25708
		Pressure hose		12,5 m, synthetic, with coupling Storz C, Ø 38 mm	JP50298
				15 m, synthetic, with coupling Storz C, Ø 52 mm	JP00336
	⑥ Chain		certified, 2.5 m, 320 kg, 5 rings (EN 818 mod.)		JP45901
			certified, 5.0 m, 320 kg, 8 rings (EN 818 mod.)		JP45902
			certified, 7.5 m, 320 kg, 11 rings (EN 818 mod.)		JP47365
			Shackle, certified, 630 kg, stainless steel		JP45904
	⑦ Guide rail system	GR 50			JP25593
		Securing lever	UV 600		JP49171
		Guide rail 1"	1500 mm		JP48937
		Guide rail 1"	2000 mm		JP48938
		Guide rail 1"	2500 mm		JP48939
		Guide rail 1"	3000 mm		JP48940




ELECTRICAL ACCESSORY

Alarm unit			Code No.
	PTS.SA1	Level alarm system with battery backup 320x240x150mm (WxDxH)	PTS.SA1
	PTS.HLA	High Level alarm unit. 182x180x111mm (HxWxD)	PTS.HLA
	Power Isolation Alarm	Isolate appliance - in event of alarm no more water will be fed into the alarm system	P734

MULTIDRAIN UV 600

SUBMERSIBLE DRAINAGE PUMPS

ELECTRICAL ACCESSORY

		Code No.			
	b Control for single units Control unit AD 46 Control unit 1-46 Control unit AD 610 Control unit HIGHLOGO 1-610 Control unit ND 3A	400 V, subm. ball contact switch 9.5 m, alarm	JP14353 JP47990 JP14354 JP47991 JP16717		
		Control for duplex units Control unit BD 46 Control unit HIGHLOGO 2-46 Control unit BD 610 Control unit HIGHLOGO 2-610	400 V, for pumps US 251-253, UV 620-3, UV 625-3 400 V 400 V, for pumps UV 635-3 400 V	JP45739 JP47999 JP45741 JP48000	
		Level control Subm. switch pack AmG Subm. switch pack BmG	3 subm. ball contact switch with 9.5 m and counterweight	JP16719 JP16726	
				Protective motor plug CEE motor protection 6,0-9,0 A CEE motor protection 4,0-6,0 A	400 V, mandatory for pumps with integrated motor protection 400 V, mandatory for pumps without integrated motor protection
		c Rechargeable battery		for mains independent alarm	JP44850

MULTIDRAIN UV 600

SUBMERSIBLE DRAINAGE PUMPS