



The floor-level shower - the dream of all bathroom owners. The floor drainage pump Plancofix can be easily integrated in any existing building without the required gradient. It transports the shower water into the nearest existing drain, from where it flows down ii's own natural way.

# More than just elegant

Floor-level showers offer much more than just showering in an elegant ambiance:

### User-friendliness

Optimal for old or handicapped people. With no step reqired, they can enter the shower without any problems.

### A new spaciousness

Optimal for old or handicapped people. With no step required, they can enter the shower without any problems.

### Technically top

- 0 max for showers up to 20 l/min.

- H max **1.30 m** 

- Performance 30 W


- Installation depth 90 mm (without insulation tray)

 Noise emission < 30 dB (A)</li>
very quiet, therefore suitable for apartment buildings


Sealing fleece according to DIN 18534
Leak tightness class W 3-I
Tear strength class R 3-I

# Centered on linear shower drain

We have extended the Plancofix range to the Plancofix Line. It features the following advantages: the floor tiler needs to integrate the slope into the shower drain direction only. Complicated tile cutting to lead the water into the drainage points drain is not more necessary. Due to its close top the wall installation of the floor drain, the showering person does not need to stand on it anymore.



Quick and easy tiling works at line drainage because just one **one slope direction** is required. The channels themselves need a minimum slope to the center.



The shower channel comes with a length of **1.20 m** and can easily be shortened to an individual length.



