




FOULMASTER

Effluent or Waste Water Pumping System



Dual Package System

Three styles of the **FOULMASTER** pumps are available; Vortex, Channel and Grinder. Our sales staff will be pleased to assist you in selecting the correct pump for your specific application.

The chamber of the **FOULMASTER** pump is fitted with one inlet, one outlet and one cable duct, pedestrian loading manhole cover and frame in mild steel galvanised (supplied loose) as standard.

All inlet connections are positioned to your specification for ultimate ease of installation. Additional inlets and heavy duty covers are available as options.

Single Pump System Features

- 1 GRP sump with manhole cover/frame inlets & cable ducts fitted and positioned to suit
- 1 Submersible pump selected for application fitted with quick release coupling or GR system
- 1 Range UPVC or ductile iron pipework
- 1 Brass Reflux valve
- 1 Brass Gate valve
- 2 Pendant level control switches
- 1 Automatic control panel with alarm

Dual Pump System Features

- 1 GRP sump with manhole cover/frame inlets & cable ducts fitted and positioned to suit
- 2 Submersible pumps selected for application fitted with quick release coupling or GR system
- 1 Range UPVC or ductile iron pipework
- 2 Brass Reflux valves
- 1 Brass Gate valve
- 1 Dual automatic control panel
- 3 Pendant level control switches

Bespoke chamber sizes:

diameter 1000mm	Variable depth
diameter 1250mm	Variable depth
diameter 1500mm	Variable depth
diameter 1800mm	Variable depth
diameter 2100mm	Variable depth
diameter 2500mm	Variable depth



▶▶▶▶▶▶▶▶▶▶ THE BETTER DECISION

The **FOULMASTER** is a packaged system designed to remove sewage or storm water from below gravity sewer level. The system alleviates the need for costly civil work. Typical applications include houses, flats, restaurants, trade/commercial parks, hotels, underpasses and motorway rest areas.


We have numerous combinations of the **FOULMASTER** to suit every possible application. Our technical sales office are able to offer assistance in system selection.



Dual Automatic Control Panel

We are able to supply the complete package including design, sales, installation, commissioning and maintenance.

PTS Control Panel (available for both single and 3 Phase systems, 8 variants)



Pump performance is subject to ISO 2548 tolerances. We reserve the right to change specifications without notice.

Foulmaster Sewage Pumping System

Type	Standard Arrangement	
PT100-US73	Single Pump	Vortex
PT100-25/2/ME	Single Pump	Grinder
PT100-08M	Single Pump	Grinder
PT100-08M	Dual Pumps	Grinder
PT150-25/4/CW1	Dual Pumps	Vortex
PT150-25/4/B4	Dual Pumps	Channel
PT180-75/4/CW2	Dual Pumps	Vortex

Performance

Delivery Head (m)	2	4	6	8	10	12	14	16	18	20	22
US73D	20	15	10	6							M3/h
UAK25/2/ME	17	17	17	17	16	15	12.5	11	9	5.5	3.5
UAK08M	16	15.5	14	12	10	8	5	2			
UAK25/2/AW	53	43	35	29	24	19	13	5			
UAK25/4/B4	114	97	77	53	31						
UAK25/4/CW1	80	61	42	23							
UAK75/4/CW2	158	135	115	97	79	69	47	13			

Pump Type

Type of Current	Voltage	kw Input	kW Output	RPM	FLC Amp	Max Solids	
US73E-D	1 or 3-phase	230 or 400v	0.83-0.85	0.50-0.60	280-2800	3.9 or 1.4	30mm
UAK25/2/ME-M	1 or 3-phase	230 or 400v	2.7-2.6	2.00-2.10	2800	12.6 or 4.4	Grinder
UAK08ME-M	1 or 3-phase	230 or 400v	1.37-1.65	1.24-0.98	2674-2705	6.0 or 2.8	Grinder
UAK25/2/AW	3-phase	400v	2.6	2.20	2800	4.4	65mm
UAK25/4/B4	3-phase	400v	2.7	2.10	1320	4.6	70mm
UAK25/4/CW1	3-phase	400v	2.7	2.10	1320	4.6	100mm
UAK75/4/CW2	3-phase	400v	7.2	6.30	1425	7.3	100mm

PUMP TECHNICAL SERVICES LIMITED

Pump House, Unit 12, Bilton Road Industrial Estate, Erith, Kent, DA8 2AN Telephone: 01322 357080

Email: sales@pts-jung.co.uk Website: www.pts-jung.co.uk

THAT'S WHAT WE ARE

